


**AFMETINGEN:** (mm)

DN	QR	L	A	B	ØD	H1	H2	H3	Kg
15	150	115	49,0	81,5	125	88,5	26,5	19,0	4,6
20	150	120	55,5	81,5	125	93,0	26,5	19,0	5,2
25	150	125	51,5	81,5	125	99,5	26,5	19,0	6,1
32	150	130	53,0	81,5	125	112,0	26,5	19,0	7,8
40	150	140	61,0	81,5	125	117,0	26,5	19,0	9,4
50	150	150	62,0	81,5	125	125,0	26,5	19,0	11,5
65	150	170	81,5	81,5	125	148,0	26,5	19,0	14,2
80	150	180	79,0	81,5	125	158,5	26,5	19,0	17,2
100	210	190	94,0	75,5	160	184,0	28,6	34,4	25,2
125	210	325	120,5	75,5	160	225,0	28,6	34,4	38,7
150	210	350	155,0	75,5	160	250,0	28,6	34,4	54,8
200	550	400	190,0	103,0	300	289,0	40,5	47,5	91,8

De wormkast is berekend met een veiligheidsfactor van 30% en een maximale verschilddruk van 16 bar.

**TOEBEHOREN:**

Eindeloopschakelaars, vastzetinrichting, kettingwiel.