


AFMETINGEN: (mm)

DN	Ø	A	L	B	EL	C	D	E	Kg
15	1/2"	50	115	29,0	EL55	69,0	324,0	95	9,3
20	3/4"	52	120	32,0	EL55	72,0	327,0	95	10,1
25	1	52	125	36,0	EL55	76,0	331,0	95	10,8
32	1 1/4"	54	130	54,0	EL55	104,0	359,0	95	13,5
40	1 1/2"	55	140	64,5	EL55	114,5	432,5	95	15,2
50	2	61	150	72,0	EL55	122,0	377,0	95	17,9
65	2 1/2"	75	170	83,5	EL100	143,5	435,5	120	28
80	3	78,5	180	95,5	EL150	155,5	447,5	120	32,8
100	4	90	190	125,0	EL200	205,0	520,0	140,5	43,9
125	5	141	325	151,0	EL500	231,0	549,0	166	77,1
150	6	160	350	170,0	EL500	250,0	568,0	166	101,7
200	8	200	400	224,0	EL800	304,0	660,0	166	138,6

De elektrische bediening is berekend met een veiligheidsfactor van 30% en een maximale verschuldruk van 16 bar.

TOEBEHOREN:

2 extra eindeloopschakelaars, potentiometer, snelheidsregelplaat, klepstandsteller.