

**Fig. 38001:** Messing schuifafsluiter - PN 10

**AANSLUITING:** BSP binnendraad

**AFMETINGEN EN GEWICHTEN:** (Afmetingen in mm.)

Diam.	L	H	Kg.
3/8"	32	70	0,170
1/2"	38	70	0,180
3/4"	40	76	0,200
1"	44	80	0,280
1 1/4"	46	94	0,400
1 1/2"	55	110	0,600
2"	60	140	0,950



**Fig. 39002:** Messing schuifafsluiter - PN 16

**AANSLUITING:** BSP binnendraad

**AFMETINGEN EN GEWICHTEN:** (Afmetingen in mm.)

Diam.	L	H	Kg.
3/8"	34	61	0,170
1/2"	39	70	0,200
3/4"	42	80	0,290
1"	47	90	0,390
1 1/4"	52	105	0,620
1 1/2"	56	125	0,800
2"	63	140	1,300
2 1/2"	64	180	2,000
3"	74	200	2,650
3 1/2"	80	224	3,700
4"	84	240	4,400



**Fig. 39302:** Messing schuifafsluiter - PN 20

**AANSLUITING:** BSP binnendraad

**AFMETINGEN EN GEWICHTEN:** (Afmetingen in mm.)

Diam.	L	H	Kg.
3/8"	42	61	0,200
1/2"	44	70	0,220
3/4"	49	85	0,320
1"	53	90	0,430
1 1/4"	61	110	0,670
1 1/2"	68	125	0,900
2"	73	140	1,330
2 1/2"	79	180	2,250
3"	84	200	3,150
4"	100	255	5,350
5"	113	300	8,500
6"	119	360	12,500

