

BRONZENTERUGSLAGKLEP MET OP- EN NEERGAANDE KLEP PN 25 FIG. 75321
UITVOERINGEN:
01: met metalen dichtingsring

02: met verwisselbare klepring in PTFE

03: met verwisselbare klepring in roestvaststaal

AANSLUITING: BSP binnendraad.

AFMETINGEN EN GEWICHTEN: (afmetingen in mm.)

Diam.	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
L H	46	46	55	63	74	92	98	113	145	170	210
Kg.	32	32	34	42	50	60	65	75	85	125	155
	0.25	0.25	0.27	0.47	0.72	1.16	1.50	2.25	3.95	6.20	11.90


MESSING TERUGSLAGKLEP MET SCHARNIERENDE KLEP PN 10 FIG. 77104
UITVOERINGEN:
01: met metalen dichtingsring

02: met verwisselbare klepring in rubber

AANSLUITING: BSP binnendraad.

AFMETINGEN EN GEWICHTEN: (afmetingen in mm.)

Diam.	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	5"	6"
L H	44	50	61	65	80	85	105	121	150	185	235	265
Kg.	33	38	42	47	54	62	70	82	95	110	220	250
	0.15	0.19	0.31	0.41	0.66	0.78	1.15	2.21	3.63	5.70	10.50	12.60


MESSING TERUGSLAGKLEP PN 16 FIG. 77601

Voor horizontale en verticale inbouw.

MATERIALEN:

Huis in messing.

Klep in hostaform.

Dichtingsring in nitril rubber.

AANSLUITING:

BSP binnendraad.

AFMETINGEN EN GEWICHTEN: (afmetingen in mm.)

Diam.	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
H	45	48	52	58	65	70	78	92	102	116
Kg.	0.15	0.17	0.29	0.49	0.68	0.85	1.36	1.48	1.81	3.12

